



PoE Layer 2 Switch

CS-L02006 DATASHEET

| | |
|-------------------------------|---|
| Port | 6x 10/100Mbps RJ45 Port |
| Standard | IEEE802.3, IEEE802.3u, IEEE802.3z, IEEE802.3ab, IEEE802.3x, IEEE802.3af, IEEE802.3at |
| PoE Port | Port 1-4 |
| PSE Power on RJ-45 | Mode A 1/2(+)/3/6(-) |
| PoE output per port | Max 32W |
| PoE Power output | Per port 55V DC Max.32W |
| VLAN Function | Support |
| Forwarding Mode | Store-and-Forward |
| Switching Capacity | 1.2G |
| MAC Address table | 2K Auto-learning Auto-aging |
| Jumbo frames | 2KByte |
| Buffer | 768Kbit |
| Forwarding Rate | 0.89Mpps |
| Input Power Supply | DC: 55V/1.1A 55V/2.3A(Optional) |
| Operation Temperature | 0°C-40°C |
| Storage Temperature | -40°C-70°C |
| Operation Humidity | 10%-90%RH non-condensing |
| Storage Humidity | 5%-90%RH non-condensing |
| Dimension (L*W*H) | 160*92.5*28mm |
| Fan | Fanless |
| Weight | <1 kg |
| LED Indicator | PWR DATA PoE Max |
| Network Media (Cable) | 10base-T: UTP category 3/5 cable (<100m) 100base-TX: UTP category 5/5e cable (<100m) |
| Surge Protection | ±4KV |
| Certification | CE, FCC Class B |
| MTBF | >50000 hour |
| Electrostatic standard | Contact 4KV air 6KV |